

BELDON



BNPP-991

Thermal Receipt Printer

- ▶ Multiple interface connections, auto-cutter, wall mountable.
- ▶ Support both 58mm and 80mm width paper. (300mm/s support)
- ▶ Support page mode. (300mm/s support)
- ▶ Support QR Code and PDF417.
- ▶ Queuing up function. (USB+Lan, USB+Serial+Lan)
- ▶ Compatible with ESC/POS commands.
- ▶ Support Windows, Linux, Android, IOS, OPOS, and MAC OS

BNPP-99I

Thermal Receipt Printer

Printing method	Direct thermal
Printing speed	250 mm/s 260 mm/s 300 mm/s
Paper width	80mm
Column capacity	576 dots/line or 512 dots/line
Interface	USB+Serial USB+Lan USB / Lan USB+Serial+Lan USB+Serial+Lan
Line spacing	5.75 mm(Adjustable by commands)
Character size	ANK, Font A: 1.5-5.0mm (12-24 dots) Font B:1.1-2.1mm (9-17 dots)Simplified/Traditional Chinese: 5.0-5.0mm (24-24 dots)
Extension character sheet	PC857 (Std.Europe) / (Katakana) / PC850 (Multilingual) / PC860 (Portugal) / PC865 (Canadian) / PC865 (Nordic) / (West Europe) / (Greek) / (Hebrew) / (East Europe) / (Iran) / (WPC1252) / PC866 (Cyrillic62) / PC852 (Latin 2) / (PC858) / (IranI) / (Latvian) / (Arabic) / (PT1511251)
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/ CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE/ PDF417
Input buffer	USB / USB+Serial: 96 Kbytes Lan / USB+Lan 256 Kbytes 256 Kbytes 4096 Kbytes
NV Flash	256 Kbytes

BNPP-99I

Thermal Receipt Printer

Power adaptor Input	AC 100 -240V, 50 -60 Hz
Printer Input	DC 24V/2.5A
Cash drawer	DC 24V/1A
Weight	0.96Kg
Dimensions	180*140*154mm
Work environment	Temperature (0 -ç5 C), humidity(10 -80%)
Storage environment	Temperature(-10 -60°C), humidity(10 -90%)
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150 Km
Emulation	ESC/POS
Driver	Windows/JPOS/Linux/OPOS/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS, Android, Windows



Scan QR code to checkout Beldon website for more update information

Phone :+44 7950 136176

info@beldonpos.com.

